

Kynol Fiber Packing


Code: KXTP605



Description

Braided from high-performance Kynol™ (Novolid™ or Phenolic™) fiber impregnated with PTFE lubricant, good mechanical properties combining softness and strength.

We call it "GOLDEN Packing".



Item no.: KXTP605

Kynol Fiber Packing

Item no.: KXTP605

- * High dimensional stability and superior pressure resistance even at elevated temperature
- * Good process-ability, easy to cut and fit
- * Thermal stability, low heat expansion
- * Outstanding chemical resistance particularly in acidic media
- * Excellent resistance to organic solvents, oil and fuels

Typical Application

* High performance packing that is well suited to applications where graphite impregnation may not be acceptable.

* Suitable for abrasive media, and where contamination is not permitted.

* Used in chemical plants and pulp and paper mills, rotating and reciprocating pumps, washer journals, liquor pumps, refiners.

Technical Data

Material	100% Kynol fiber and PTFE
Temperature Range	-200 up to +260 oC atmosphere
Rotating	20 bar
Reciprocating	100 bar
Static	200 bar
Shaft Speed	20 m/s in rotary
PH	1~13
Density	1.5g/cm ³

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:sales@seal-china.com,kaxite@seal-china.com